



US Drives, Inc.
2221 Niagara Falls Boulevard
P.O. Box 281
Niagara Falls, NY 14304-0281
Tel: (716) 731-1606
Visit us at www.usdrivesinc.com

Phoenix DS Clean Power (18 Pulse) AC Drive

Poor power quality can be costly. Nonlinear loads, including AC Drives, introduce undesirable harmonic currents into the power system that can damage equipment, increase downtime and ultimately drive up the cost of your electric utility bill. With electric utility deregulation, more attention is now being paid to peak demand charges, power factor penalties and the added cost of harmonic distortion.

That's why we designed the Phoenix DS Clean Power AC Drive. The Phoenix DS Clean Power AC Drive uses 18 Pulse rectifications to minimize both the voltage and current harmonic distortion on the AC power line. In fact, the Phoenix DS Clean Power AC Drive meets the stringent requirements of IEEE 519 1992 without the use of any additional external filters, line reactors or drive isolation transformers. You get all the economic advantages of an AC Drive, reduced inrush current demand and improved power factor, without the harmonics.

With all these real world benefits and with new economic penalties tied to power quality, it's easy to understand why more and more people are turning to the Phoenix DS Clean Power AC Drive.



POWER QUALITY:

- **Meets IEEE 519 1992 for both voltage and current harmonic distortion.**
- **No need for external filters - no matter where the drive is placed in the plant.**
- **Eliminates the need for expensive and time consuming harmonic analysis.**
- **Avoids resonance problems associated with inefficient harmonic filters.**
- **Prevents overloading of circuit breakers and feeders.**
- **Avoids transformer overheating.**
- **Eliminates penalties for poor power factor from utility company.**
- **Can be run off Motor / Generator systems with near zero harmonic distortion.**

THREE YEAR WARRANTY

MADE IN USA



US Drives, Inc.
 2221 Niagara Falls Boulevard
 P.O. Box 281
 Niagara Falls, NY 14304-0281
 Tel: (716) 731-1606
 Visit us at www.usdrivesinc.com

ENGINEERING SPECIFICATIONS

CONTROL

Control Method: Sine coded PWM with programmable carrier.
 Space Vector control.

Output Voltage: 0 to rated voltage

Output Frequency Range: 0 to 600 Hz.

Frequency accuracy: Analog reference: 0.1% of max frequency.
 Digital reference: 0.01% of max frequency.

Frequency resolution: Analog reference: 0.06Hz at 60Hz.
 Digital reference: 0.001Hz at 60Hz.

Accel / Decel: Adjustable 0.1 to 3276 sec.

Drive Overload: High Overload Capacity Drives:
 150% of drive rated output for one (1) minute.
 Normal Overload Capacity Drives:
 120% of drive rated output for one (1) minute.

Inverse Time Overload: Programmable for class 10, 20 and 30 protection with speed sensitive protection to comply with N.E.C. Article 430.

Current limit: Proactive current limit programmable in % of motor rated current.

Braking torque: 5 to 20% without modification. Braking modules available for added braking to 150%

ELECTRICAL

Rated Input Voltage: 200-250Vac, 380-500Vac, 500-600Vac
 -10% of minimum, +10% of maximum.

Rated Input Frequency: 48 to 63Hz

Number of Phases: 3

Displacement Power Factor: .95 or greater

Efficiency: 97% or greater at rated current

ENVIRONMENTAL

Ambient Temperature: -10°C to 50°C (14°F to 122°F)
 without derating.

Storage Temperature: -40°C to 70°C (-40°F to 158°F)

Altitude: Sea level to 3300 Feet [1000m]
 without derating.

Humidity: 95% relative humidity non-condensing.

Vibration: 9.8m/sec² (1.0G) peak.

Surge Protection: Line Transients to 6000V
 IEEE C62.41-1991 Category B
 Showering Arc - 2000V Peak
 EN50082 - 1, 2

Input R.F.I Filter: Standard on all models.

AVAILABLE OPTIONS

- Signal Conditioners/Isolators
- Communications Cards: RS-232/422/485, Modbus RTU
- Analog Signal Conditioner/Isolation Cards
- Digital Input/Output Expansion/Conditioning Cards
- Hand/Off Auto, Local/Remote, Auto/Manual Selection
- Many Additional Modifications Available

PHYSICAL ATTRIBUTES

Mounting: Wall Mount: Through hole or panel mount.

Nema Rating: Type 1 (IP20) as Standard
 Type 12 (IP54) Optional
 Type 4 (IP65) Optional

Construction: Steel Enclosure (Reduces E.M.I.)

380-500VAC (-10% to +10%) ¹						
NEMA 1 Catalog Number ²	Motor HP ³	Continuous Output Current ⁴ (Amps)	Output KVA ⁵	Input Current (Amps)	Input KVA ⁵	Dimensions ⁶ HxWxD
D4-0040xx-N1-CP	40	52	43	43	36	60x24x23
D4-0050xx-N1-CP	50	66	55	54	45	60x24x23
D4-0060xx-N1-CP	60	82	68	65	54	60x24x23
D4-0075xx-N1-CP	75	97	81	81	68	72x30x25
D4-0100xx-N1-CP	100	124	103	108	90	72x30x25
D4-0125xx-N1-CP	125	156	130	135	113	72x30x25
D4-0150xx-N1-CP	150	180	150	162	135	72x30x25
D4-0200xx-N1-CP	200	240	200	217	180	72x30x25
D4-0250xx-N1-CP	250	302	251	271	225	72x72x30
D4-0300xx-N1-CP	300	361	300	325	270	72x72x30
D4-0350xx-N1-CP	350	414	344	379	315	72x72x30
D4-0400xx-N1-CP	400	477	397	433	360	72x72x30
D4-0450xx-N1-CP	450	540	449	487	405	72x72x30
D4-0500xx-N1-CP	500	600	499	541	450	72x72x30
D4-0600xx-N1-CP	600	720	599	650	540	84x118x30
D4-0700xx-N1-CP	700	840	698	758	630	84x118x30
D4-0800xx-N1-CP	800	960	798	866	720	84x118x30

(1) Consult Factory for higher HP Drive Information and for 200-250VAC and 500-600VAC Drive Information.
 (2) "xx" = CT for High Overload Capacity Drives, "xx" = VT for Normal Overload Capacity Drives.
 (3) Horsepower rating is based on 460 VAC Motors.
 (4) High Overload Capacity Drives produce 150% of Rated Drive Output Current for 1 minute; Normal Overload Capacity Drives produce 120% of Rated Drive Output Current for 1 minute.
 (5) Output and Input KVA are calculated at 480Vac.
 (6) All dimensions in inches.