



US Drives Inc.  
2221 Niagara Falls Boulevard  
P.O. Box 281  
Niagara Falls, NY 14304-0281  
Tel: (716) 731-1606 Fax: (716) 731-1524  
Visit us at [www.usdrivesinc.com](http://www.usdrivesinc.com)

## Phoenix EX Sensorless AC Vector Drive



**3 HP to 3500 HP**

### Standard Features:

- \* OPEN OR CLOSED LOOP VECTOR CONTROL
  - \* EASY TO USE, SIMPLE SETUP
  - \* PRECISE CONTROL OF MOTOR SPEED AND TORQUE
  - \* BACKLIT ENGLISH LANGUAGE DISPLAY
  - \* 50°C AMBIENT TEMPERATURE RATING
  - \* SHORT CIRCUIT AND GROUND FAULT PROTECTION
  - \* BUILT IN LINE VOLTAGE SURGE PROTECTION
  - \* TOLERATES HIGH INPUT AC LINE VOLTAGES
  - \* MOTOR OVERLOAD PROTECTION, MEETS NEC 430
  - \* BUILT IN RFI NOISE FILTER
  - \* POWER DIP RIDE THROUGH
  - \* AUTO RESTART
- \* HIGH PERFORMANCE PID CONTROL
  - \* 8 PRESET SPEEDS WITH ACCEL/DECEL CONTROL
  - \* S CURVE ACCEL/DECEL CONTROL
  - \* MULTI FUNCTION I/O
  - \* PROGRAMMABLE THRESHOLD DETECTORS
  - \* KW / KWH METERING
  - \* BI-DIRECTIONAL FLYCATCHER (CATCH SPINNING MOTOR)
  - \* CUSTOM V/Hz PROGRAMMING
  - \* AUTOLOGGING FAULT HISTORY
  - \* FIXED OR VARIABLE CARRIER FREQUENCY
  - \* MUCH, MUCH, MORE..



**THREE YEAR WARRANTY**

**MADE IN USA**



US Drives Inc.  
 2221 Niagara Falls Boulevard  
 P.O. Box 281  
 Niagara Falls, NY 14304-0281  
 Tel: (716) 731-1606 Fax: (716) 731-1524  
 Visit us at www.usdrivesinc.com

# ENGINEERING SPECIFICATIONS

## CONTROL

**Speed Range:** Open Loop: 100:1  
 Closed Loop: 1000:1

**Control Modes:** Speed Control  
 Torque Control  
 Speed Control with Torque Limit  
 Torque Control with Speed Limit

**Control Method:** Sine coded PWM with programmable carrier.  
 Open Loop/Closed Loop Vector Control.

**Output Voltage:** 0 to input voltage

**Output Frequency Range:** 0 to 600 Hz.

**Frequency accuracy:** Analog reference: 0.1% of max frequency.  
 Digital reference: 0.01% of max frequency.

**Frequency resolution:** Analog reference: 0.06Hz at 60Hz.  
 Digital reference: 0.0005Hz at 60Hz.

**Accel / Decel:** Adjustable 0.1 to 3276 sec.

**Drive Overload:** High Overload Capacity Drives:  
 150% of drive rated output for one (1) minute.  
 Normal Overload Capacity Drives:  
 120% of drive rated output for one (1) minute.

**Inverse Time Overload:** Programmable for class 10, 20 and 30 protection with speed sensitive protection to comply with N.E.C. Article 430.

**Current limit:** Proactive current limit programmable in % of motor rated current.

**Braking torque:** 5 to 20% without modification. Braking modules available for added braking to 150%

**Control power ride-thru:** Two (2) seconds or greater, depending on load.

## ELECTRICAL

**Rated Input Voltage:** 200-250Vac, 380-500Vac, 500-600Vac  
 -10% of minimum, +10% of maximum.

**Rated Input Frequency:** 48 to 63Hz

**Number of Phases:** 3

**Displacement Power Factor:** .95 or greater

**Efficiency:** 97% or greater at rated current

## ENVIRONMENTAL

**Ambient Temperature:** -10°C to 50°C (14°F to 122°F) without derating.

**Storage Temperature:** -40°C to 70°C (-40°F to 158°F)

**Altitude:** Sea level to 3300 Feet [1000m] without derating.

**Humidity:** 95% relative humidity non-condensing.

**Vibration:** 9.8m/sec<sup>2</sup> (1.0G) peak.

**Surge Protection:** Line Transients to 6000V  
 IEEE C62.41-1991 Category B

**Noise Immunity:** Showering Arc - 2000V Peak  
 EN50082 - 1, 2

**Input R.F.I Filter:** Standard on all models.

## PHYSICAL ATTRIBUTES

**Mounting:** Wall Mount: Through hole or panel mount.

**Nema Rating:** Type 1 (IP20) as Standard  
 Type 12 (IP54) Optional  
 Type 4 (IP65) Optional

**Construction:** Steel Enclosure (Reduces E.M.I.)

## AVAILABLE OPTIONS

- Encoder Feedback Card
- Signal Conditioners/Isolators
- Communications Cards: RS-232/422/485, Modbus RTU, Metasys N2 & Others
- Analog Signal Conditioner/Isolation Cards
- Digital Input/Output Expansion/Conditioning Cards
- Hand/Off Auto, Local/Remote, Auto/Manual Selection
- Many Additional Modifications Available

Phoenix EX AC Drive Dimensions<sup>1</sup>

Input Voltage	Motor HP <sup>2</sup>		Nema 1 VFD Only	Nema 12 VFD Only	Nema 1 w Disconnect & Fuses	Nema 12 w Disconnect & Fuses	Nema 1 with Bypass	Nema 12 with Bypass
	High Overload Capacity <sup>3</sup> (HT)	Normal Overload Capacity <sup>4</sup> (NT)						
200 - 250 VAC (208/230/240)	3 - 7.5	5 - 10	13.05"x9.0"x10.9"	13.05"x9.0"x10.9"	20.74"x9.0"x10.9"	20.74"x9.0"x10.9"	34.02"x9.0"x10.9"	34.02"x9.0"x10.9"
	10 - 20	15 - 20	13.05"x9.0"x10.9"	13.05"x9.0"x10.9"	20.74"x9.0"x10.9"	20.74"x9.0"x10.9"	34.02"x9.0"x10.9"	34.02"x9.0"x10.9"
	25 - 30	25 - 30	25"x11.6"x11.1"	25"x11.6"x11.1"	25"x11.6"x11.1"	25"x11.6"x11.1"	38.4"x11.6"x11.1"	38.4"x11.6"x11.1"
	40 - 100	40 - 100	32.5"x20.1"x13.5"	32.5"x20.1"x13.5"	32.5"x20.1"x13.5"	32.5"x20.1"x13.5"	65"x20.1"x13.5"	60"x36"x16"
	125 - 250	125 - 250	44.2"x31.1"x16.8"	44.2"x31.1"x16.8"	72"x36"x23.5"	72"x36"x23.5"	72"x72"x23.5"	72"x72"x23.5"
380 - 500 VAC (380/400/415/480)	5 - 15	7.5 - 20	13.05"x9.0"x10.9"	13.05"x9.0"x10.9"	20.74"x9.0"x10.9"	20.74"x9.0"x10.9"	34.02"x9.0"x10.9"	34.02"x9.0"x10.9"
	20 - 40	25 - 40	13.05"x9.0"x10.9"	13.05"x9.0"x10.9"	20.74"x9.0"x10.9"	20.74"x9.0"x10.9"	34.02"x9.0"x10.9"	34.02"x9.0"x10.9"
	50 - 60	50 - 60	25"x11.6"x11.1"	25"x11.6"x11.1"	25"x11.6"x11.1"	25"x11.6"x11.1"	38.4"x11.6"x11.1"	38.4"x11.6"x11.1"
	75 - 200	75 - 200	32.5"x20.1"x13.5"	32.5"x20.1"x13.5"	32.5"x20.1"x13.5"	32.5"x20.1"x13.5"	65"x20.1"x13.5"	60"x36"x16"
	250 - 500	250 - 500	44.2"x31.1"x16.8"	44.2"x31.1"x16.8"	72"x36"x23.5"	72"x36"x23.5"	72"x72"x23.5"	72"x72"x23.5"
525 - 600 VAC (525/575/600)	5 - 15	7.5 - 20	13.05"x9.0"x10.9"	13.05"x9.0"x10.9"	20.74"x9.0"x10.9"	20.74"x9.0"x10.9"	24"x24"x14.2"	24"x24"x14.2"
	20 - 40	25 - 40	13.05"x9.0"x10.9"	13.05"x9.0"x10.9"	20.74"x9.0"x10.9"	20.74"x9.0"x10.9"	24"x30"x14.2"	24"x30"x14.2"
	50 - 75	50 - 75	25"x11.6"x11.1"	25"x11.6"x11.1"	25"x11.6"x11.1"	25"x11.6"x11.1"	38.4"x11.6"x11.1"	38.4"x11.6"x11.1"
	100 - 200	100 - 200	32.5"x20.1"x13.5"	32.5"x20.1"x13.5"	32.5"x20.1"x13.5"	32.5"x20.1"x13.5"	65"x20.1"x13.5"	60"x36"x16"
	250 - 600	250 - 600	44.2"x31.1"x16.8"	44.2"x31.1"x16.8"	72"x36"x23.5"	72"x36"x23.5"	72"x72"x23.5"	72"x72"x23.5"

(1) All Dimensions in Inches (HxWxD)  
 (2) Horsepower Rating based on 230, 460, and 575VAC Motors  
 (3) High Overload Capacity Drives produce 150% of Rated Drive Output Current for 1 minutes  
 (4) Normal Overload Capacity Drives produce 120% of Rated Drive Output Current for 1 minutes  
 (5) Consult Factory for Higher HP Drive Dimensions